




www.catpowertools.com
©2021 Caterpillar. CAT. CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge"
trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may
not be used without permission.



CAT® POWER TOOLS FROM THE BRAND **YOU CAN TRUST**

In every corner of the world ,you'll find a Cat® machine.

Cat[®] is recognized as the leader in building and construction. Globally, the Cat[®] logo has become an icon, often worn as a badge symbolizing grit, toughness and a get-it-done attitude.

Cat[®] products are engineered for superior performance, designed to last, and backed by the largest, most experienced dealer support network in the world.

BRUSHLESS MOTORS



Best-in-class brushless motor and precise electrical control technology deliver the ultimate performance, durability and run-time.

OX LONGER MOTOR

Brushless motors have fewer wearable moving parts resulting in increased motor life.

Carbon brush resistance is eliminated, so less battery energy is wasted.

The efficiency of a brushless motor results in a greater run time from each charge.

Fewer moving parts results in a quiet motor that never needs maintenance. The reduced friction enables a better use of available energy from the battery pack as there is no resistance from brushes.

SHAREABLE BATTERIES & CHARGERS



All Cat® batteries and chargers are compatible across the entire line of 18V power tools. One interchangeable system charges every Cat® power tool.

BATTERY TECHNOLOGY

Cat®batteries are designed for professional applications to power heavy loads and maintain a charge during long, continuous work times. The Cat® battery protection system optimizes and

prolongs run times for maximum use and safety.

CHARGERS

Cat®lightning fast chargers fully recharge Cat®18V 5.0Ah graphene batteries in just 20 minutes.

The Cat®Charger system is designed to optimize charging by balancing the charge between each cell to maximize battery performance and run times. So your Cat® tools are always ready to go when you are.

ZSLIDE LOCK STORAGE TECH





REVOLUTIONARY 18V GRAPHENE* BATTERY TECHNOLOGY



18V 80N.m Hammer Drill DX13



FEATURE

- Revolutionary Graphene* battery technology
- High torque 80N.m for tough application
- Rubber over mould grip
- Single sleeve metal chuck
- Durable auxiliary handles to protect users from kickback
- LED light

- Brushless motor
- Two speed gear box
- Variable speed with reverse

2.8Kg

Auto spindle lock

SPECIFICATIONS

Voltage: 18V Number of clutch positions: 22+1+1
Chuck size: 13mm Max cutting capacity: wood 55mm
No load speed: 0-550/0-2200/min metal 13mm
Max torque: 80N.m masonry 16mm

Impact rate: 0-10450/41800 bpm Machine weight:

ACCESSORIES

1pc 5.0Ah Graphene* battery pack 1pc 15A Charger

1pc Belt clip 1pc Auxiliary handle

Injection carry case+Color box

^{*} Graphene polymer is integrated into the Cathode of battery cells to get enhanced performance of battery.

18V 65N.m Drill Driver **DX11**









- · Brushless motor
- Two speed gear box
- Single sleeve metal chuck
- Variable speed with reverse
- LED light

- High torque 65N.m for tough application
- Rubber over mould grip
- Auto spindle lock

18V 65N.m Hammer Drill



DX12

22+1+1









FEATURE

- · Brushless motor
- Two speed gear box
- Single sleeve metal chuck
- Variable speed with reverse
- LED light

Voltage:

- High torque 65N.m for tough application
- Rubber over mould grip
- Auto spindle lock

Number of clutch positions:

• Impact function

SPECIFICATIONS

Voltage: 18V wood 40mm Max cutting capacity: Chuck size: 13mm metal 13mm No load speed: 0-500/0-2000/min Machine weight: 1.92Kg Max torque: 65N.m Packing type: Color box Number of clutch positions: 18+1

ACCESSORIES

2pc 4.0Ah Li-ion battery pack

1pc 4A Charger

1pc Belt clip

Injection carry case

SPECIFICATIONS

Chuck size: 13mm Max cutting capacity: wood 40mm No load speed: 0-500/0-2000/min metal 13mm Max torque: 65N.m masonry 16mm Impact rate: 0-8000/0-32000bpm 1.97Kg Machine weight:

18V

ACCESSORIES

2pc 4.0Ah Li-ion battery pack

1pc Belt clip

Injection carry case+Color box

1pc 4A Charger

18V 215N.m 3 Speed Impact Driver

DX71

18V 350N.m Impact Wrench

DX72











- · Brushless motor
- Variable speed with reverse
- LED light with Pre-light function for work area
- Convenient belt clip frees your hands for multitasking



- 3-Speed design
- Rubber over mould grip















FEATURE

- Brushless motor
- 3-Speed design
- Rubber over mould grip
- Convenient belt clip frees your hands for multitasking
- LED light with Pre-light function for work area
- Variable speed with reverse

SPECIFICATIONS

Chuck size:

Voltage: 18V Impact rate: 0-1300/2900/3600bpm

Max torque: 215N.m

No load speed: 0-1300/2100/3200/min Machine weight: 1.52Kg

1/4"Hex

SPECIFICATIONS

Voltage:

18V

Max torque:

350N.m

Chuck size: No load speed:

½"Anvil 0-1300/2100/3200rpm Machine weight:

1.81Kg

Impact rate: 0-1300/2900/3600bpm Packing type: Color box

ACCESSORIES

2pc 4.0Ah Li-ion battery pack

1pc 4A charger

1pc Belt clip

Injection carry case+Color box

ACCESSORIES

2pc 4Ah battery Pack

1pc 4A charger

1pc Belt clip

1pc Dental pin for Anvil

1pc Steel O ring

Injection carry case+Color box

18V 2in1 Combo Kit (Hammer Drill & Impact Driver)



















FEATURE

DX12

- Impact function
- High torque 65N.m for tough application
- Rubber over mould grip
- Single sleeve metal chuck
- Variable speed with reverse

DX71

- 3-Speed design
- Variable speed with reverse
- Rubber over mould grip
- LED light with Pre-light function for work area
- Convenient belt clip frees hands for multitasking

SPECIFICATIONS

DX12

13mm

Chuck size:

DX71

¼"Hex

No load speed:

0-500/0-2000/min

No load speed:

0-1300/2100/3200/min

Max torque:

Chuck size:

65N.m

Max torque:

215N.m 0-1600/2900/3600bpm

Impact rate:

0-8000/0-32000bpm

Impact rate: 1pc 4A Charger

ACCESSORIES

2pc 4.0Ah Li-ion battery pack

2pc Belt clip

Injection carry case+Color box





18V 5 Function SDS Rotary Hammer





• Brushless motor

- Dual Overload protection
- 5 function: Drill, Hammer drill, Bit Rotation, Chisel, Tile Drilling SDS-plus quick change system
- Forward and reverse rotation

• Variable speed with reverse

• Anti vibration design

- Rubber over mould grip
- Electronic impulse function for easy drilling on ceramic
- LED light

SPECIFICATIONS

Voltage:	18V	Max cutting capacity:	wood 32mm
Chuck type:	SDS Plus		metal 13mm
No load speed:	0-1210/min		concrete 26mm
Impact rate:	0-5400bpm	Machine weight:	3.25Kg
Impact energy:	2.2J	Packing type:	Color box

ACCESSORIES

2pc 4.0Ah Li-ion battery pack1pc 4A Charger1pc Auxiliary handle1pc Depth gauge

Injection carry case





DX31B











FEATURE

- Brushless motor
- Overload protection
- Dust resistant with mesh filters

- Anti-restart prevent accident start
- Rubber over mould grip
- Quick guard adjustment
- Slim body design with paddle switch for comfortable user experience
- Anti-vibration auxiliary handle

SPECIFICATIONS

Voltage:18VDisc bore:22.2mmDisc Size:115mmMachine weight:1.9Kg BareNo load speed:8500/minPacking type:Color box

•

Spindle thread: M14

ACCESSORIES

1pc Grinding guard

1pc Auxiliary handle

1pc Spanner



18V 26mm Jig Saw DX51B















- · Brushless motor
- Tool-free base bevel adjustment
- Rubber over mould grip
- Lock-off switch prevents accidental starting
- 4-Stage Pendulum settings for improved cutting efficiency

- Variable speed
- Tool-free blade change system
- SDS Adjustable base for angle cutting

18V 185mm Circular Saw



Lock-off switch

• Rubber over mould grip

• LED light

DX53B



- Spindle lock
- Hex key storage

- · Brushless motor

- Metal rafter hook
- Overload protection & Electronic brake
- Magnesium alloy base & Aluminum guard for strong & light weight design

SPECIFICATIONS

	1pc Blade for wood	1pc Parallel guide	
		Packing Type:	Color box
Bevel capacity:	0-45°	Machine weight:	1.9Kg Bare
No load speed:	0-3500/min		PVC pipe 20mm
Stroke length:	26mm		steel 10mm
Voltage:	18V	Max cutting capacity:	wood 120mm

1pc Dust adapter

1pc Base cover

SPECIFICATIONS

Voltage: 18V Max cutting capacity: 45° 46mm Blade size: 185mm 90° 65mm No load speed: 5500/min Machine weight: 3.7Kg Bare Bevel capacity: 0-56° Packing type: Color box

ACCESSORIES

1pc Hex key 1pc Parallel guide

1pc Dust adapter

1pc 185mm*24T TCT blade

ACCESSORIES

18V Reciprocating Saw DX52B













FEATURE

- · Brushless motor
- Aluminum gear box
- Tool-free blade change system
- Tool-Less pivot foot plate adjustment
- LED light
- Metal rafter hook

- Variable speed
- Pendulum function
- Rubber over mould grip

18V Planer DX81B











FEATURE

- · Brushless motor
- Right side dust ejection port
- With Rest stand
- Micro cutting depth adjustment
- Rubber over mould grip

- Overload protection
- Aluminum base with V-groove
- On board storage space for blade & wrench

SPECIFICATIONS SPECIFICATIONS

Voltage: 18V Max cutting capacity: wood 300mm
Stroke length: 29mm metal 12mm

0-3000/min

Machine weight: 2.5Kg Bare

Packing type: Color box

Voltage: 18V Max Cutting width: 82mm

Max cutting depth: 2mm Machine weight: 2.3Kg Bare

No load speed: 15500/min Packing type: Color box

1pc Parallel guide

Max rebate depth: 8mm

1pc Rebate guide 1pc Spanner
1pc Dust bag 1pc Hex key

2pc TCT blades on machine

ACCESSORIES

No load speed:

1pc Rater hook

1pc Blade for wood

ACCESSORIES



DX41B











FEATURE

- Brushless motor
- Slim body design
- Tool less system for changing accessories
- Variable speed control
- Rubber over mould grip
- Dual LED light
- Universal interface fit for all brand all oscillating accessories
- Multi-function finishing, detail and corner sanding

SPECIFICATIONS

Voltage: 18V Machine weight: 1.7Kg Bare

Oscillation angle: 4.0° Packing type: Plastic box +Color box

No load speed: 8000-19000/min

ACCESSORIES

9pc Sanding sheet(40#/80#/120#)

1pc Rigid scraping blade

1pc HSS segment saw blade

1pc Sanding base

1pc Wood plunge cutting blade

1pc Metal cutting blade





18V 125mm Orbital Rotary Sander

DX42B













FEATURE

- Sanding and polishing 2 in 1 function
- Variable speed control
- On/off switch
- Pad brake system
- Rubber over mould grip

- Hook and loop & clamp system
- Dust collection system

SPECIFICATIONS

Voltage: 18V
Base size: 125mm(for Sanding)

Base size: 150mm(for Polishing)

No load speed: 3000-11000/min

1pc Dust bag

Orbital diameter: 2.4mm

Machine weight: 1.4Kg Bare

Packing type: Color box

ACCESSORIES 1p

1pc 150mm polishing foam pad

3pc Sanding paper(60#/80#/120#)

18V Jobsite Worklight DX62B







FEATURE

- Flood light illumination pattern with Super bright / Energry-saving model
- COB LED light ensures a long service life and minimum heat generation to touch
- Flexible operation-360 degree head rotating to freely adjust lighting angle
- Battery powered and portable handle to carry away
- Sturdy light case for tripod mountable and a variety of other hanging methods
- Sealed water Proof switch

18V Bluetooth Radio DX61B













FEATURE

- Tough & impact resistant
- USB power output for charging mobile phone
- Soft Antenna
- Digital Audio Broadcasting(DAB)
- FM/DAB (Auto Tune function & 5 stations memory)

- Aux input
- Bluetooth input
- Carry handle for easy transportation
- LCD display quality

SPECIFICATIONS

Voltage: 18V Working time with 2.0Ah battery: Rated power: 20W 1.68Kg Bare Machine weight:

Lumen: 1600/750Lumen

Bulb type: LED

Color box

Voltage: 2hr

2X5W

18V

Dustproof / waterproof: Machine weight:

4.5Kg Bare

IP54

USB port output:

Loudspeaker Power:

5V 1.0A

1pc AC power adaptor

Packing type:

Color box

DAB frequency coverage:

SPECIFICATIONS

174.928-239.200MHz

FM frequency coverage: 87.5-108MHz

ACCESSORIES

ACCESSORIES

18V 5.0Ah Graphene* Battery Pack GXB5



SPECIFICATIONS

Voltage: 18V

Battery capacity: 5.0Ah Li-ion Graphene*

Charging time: 20min

(On Charger DXC15)

Machine weight: 1.00Kg

18V 4.0Ah Battery Pack DXB4



SPECIFICATIONS

Voltage: 18V

Battery capacity: 4.0Ah Li-ion

Machine weight: 0.65Kg

18V 4.0A Charger DXC4



SPECIFICATIONS

Output voltage: 20V Battery capacity: 4.0A

Power: 95W

Charging time: 2.0Ah (DXB2) 30 mins

4.0Ah (DXB4) 60 mins

DXC15

Machine weight: 0.40Kg

18V 15.0A Charger



SPECIFICATIONS

Output voltage: 20V

Battery capacity: 15.0A

Power: 380W

Charging time: 2.0Ah (DXB2) 30 mins

4.0Ah (DXB4) 30 mins

5.0Ah (GXB5) 20 mins

Machine weight: 1.18Kg

^{*} Graphene polymer is integrated into the Cathode of battery cells to get enhanced performance of battery.



Orbital diameter

(Sheet sander)

oscillating blade

Universal interface fit for all brand

Soft start

Constant speed



NOTE

www.catpowertools.com

ICONS GUIDE

Base size

(Sheet sander)